



Jones Environmental Laboratory

Registered Address : Unit 3 Deeside Point, Zone 3, Deeside Industrial Park, Deeside, CH5 2UA. UK

Unit 3 Deeside Point
Zone 3
Deeside Industrial Park
Deeside
CH5 2UA

Dalradian Gold Ltd
3 Killybrack Rd
Omagh
BT79 7DG

Tel: +44 (0) 1244 833780
Fax: +44 (0) 1244 833781



Attention : [REDACTED]
Date : 17th May, 2016
Your reference : DCS
Our reference : Test Report 16/8520 Batch 1
Location : Curraghinalt
Date samples received : 5th May, 2016
Status : Final report
Issue : 1

Seven samples were received for analysis on 5th May, 2016 of which seven were scheduled for analysis. Please find attached our Test Report which should be read with notes at the end of the report and should include all sections if reproduced. Interpretations and opinions are outside the scope of any accreditation, and all results relate only to samples supplied. All analysis is carried out on as received samples and reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected.

Compiled By:

[REDACTED]

[REDACTED] BSc
Project Manager

Client Name: Dalradian Gold Ltd
 Reference: DCS
 Location: Curraghinalt
 Contact: ██████████
 JE Job No.: 16/8520

Report : Liquid

Liquids/products: V=40ml vial, G=glass bottle, P=plastic bottle
 H=H₂SO₄, Z=ZnAc, N=NaOH, HN=HNO₃

| J E Sample No. | 1-6 | 7-12 | 13-18 | 19-24 | 25-30 | 31-36 | 37-42 | | | | | | | | | | | | |
|--|---------------|---------------|---------------|---------------|---------------|---------------|---------------|--|--|--|--|--|--|---------|----------|------------|--|--|--|
| Sample ID | DCS1 | DCS2 | DCS3 | DCS4 | DCS5 | DCS6 | DCS7 | | | | | | | | | | | | |
| Depth | | | | | | | | | | | | | | | | | | | |
| COC No / misc | | | | | | | | | | | | | | | | | | | |
| Containers | V HN P BOD G | V HN P BOD G | V HN P BOD G | V HN P BOD G | V HN P BOD G | V HN P BOD G | V HN P BOD G | | | | | | | | | | | | |
| Sample Date | 04/05/2016 | 04/05/2016 | 04/05/2016 | 04/05/2016 | 04/05/2016 | 04/05/2016 | 04/05/2016 | | | | | | | | | | | | |
| Sample Type | Surface Water | Surface Water | Surface Water | Surface Water | Surface Water | Surface Water | Surface Water | | | | | | | | | | | | |
| Batch Number | 1 | 1 | 1 | 1 | 1 | 1 | 1 | | | | | | | | | | | | |
| Date of Receipt | 05/05/2016 | 05/05/2016 | 05/05/2016 | 05/05/2016 | 05/05/2016 | 05/05/2016 | 05/05/2016 | | | | | | | | | | | | |
| | | | | | | | | | | | | | | LOD/LOR | Units | Method No. | | | |
| Dissolved Arsenic # | 2.5 | 2.5 | 2.1 | <0.9 | <0.9 | <0.9 | 6.0 | | | | | | | <0.9 | ug/l | TM30/PM14 | | | |
| Dissolved Cadmium # | <0.03 | <0.03 | <0.03 | <0.03 | <0.03 | <0.03 | <0.03 | | | | | | | <0.03 | ug/l | TM30/PM14 | | | |
| Total Dissolved Chromium # | <0.2 | <0.2 | <0.2 | <0.2 | <0.2 | <0.2 | <0.2 | | | | | | | <0.2 | ug/l | TM30/PM14 | | | |
| Dissolved Copper # | <3 | <3 | <3 | <3 | <3 | <3 | <3 | | | | | | | <3 | ug/l | TM30/PM14 | | | |
| Total Dissolved Iron # | 1.8610 | 0.5691 | 1.0430 | 0.6549 | 0.6460 | <0.0047 | 0.5960 | | | | | | | <0.0047 | mg/l | TM30/PM14 | | | |
| Dissolved Lead # | <0.4 | <0.4 | <0.4 | <0.4 | <0.4 | <0.4 | <0.4 | | | | | | | <0.4 | ug/l | TM30/PM14 | | | |
| Dissolved Mercury # | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | <0.5 | | | | | | | <0.5 | ug/l | TM30/PM14 | | | |
| Dissolved Nickel # | <0.2 | 4.5 | 1.8 | <0.2 | <0.2 | <0.2 | 3.2 | | | | | | | <0.2 | ug/l | TM30/PM14 | | | |
| Dissolved Zinc # | <1.5 | 1.9 | 1.7 | <1.5 | <1.5 | <1.5 | <1.5 | | | | | | | <1.5 | ug/l | TM30/PM14 | | | |
| Total Zinc | <3 | <3 | <3 | <3 | <3 | <3 | <3 | | | | | | | <3 | ug/l | TM30/PM14 | | | |
| Total Hardness Dissolved (as CaCO ₃) | 21 | 190 | 102 | 26 | 29 | <1 | 212 | | | | | | | <1 | mg/l | TM30/PM14 | | | |
| EPH (C8-C40) # | <10 | <10 | <10 | <10 | <10 | <10 | <10 | | | | | | | <10 | ug/l | TM5/PM30 | | | |
| GRO (>C4-C8) # | <10 | <10 | <10 | <10 | <10 | <10 | <10 | | | | | | | <10 | ug/l | TM36/PM12 | | | |
| GRO (>C8-C12) # | <10 | <10 | <10 | <10 | <10 | <10 | <10 | | | | | | | <10 | ug/l | TM36/PM12 | | | |
| GRO (>C4-C12) # | <10 | <10 | <10 | <10 | <10 | <10 | <10 | | | | | | | <10 | ug/l | TM36/PM12 | | | |
| Hexavalent Chromium | <2 | <2 | <2 | <2 | <2 | <2 | <2 | | | | | | | <2 | ug/l | TM38/PM0 | | | |
| Total Dissolved Chromium III | <2 | <2 | <2 | <2 | <2 | <2 | <2 | | | | | | | <2 | ug/l | NONE/NONE | | | |
| BOD (Settled) # | 2 | 2 | 1 | 1 | 2 | 1 | 2 | | | | | | | <1 | mg/l | TM58/PM0 | | | |
| pH # | 6.94 | 7.36 | 7.40 | 7.08 | 7.09 | 5.93 | 7.39 | | | | | | | <0.01 | pH units | TM73/PM0 | | | |
| Total Suspended Solids # | <10 | <10 | <10 | <10 | <10 | <10 | <10 | | | | | | | <10 | mg/l | TM37/PM0 | | | |

Please see attached notes for all abbreviations and acronyms

Client Name: Dalradian Gold Ltd
Reference: DCS
Location: Curraghinalt
Contact: Shane Feehan

| J E Job No. | Batch | Sample ID | Depth | J E Sample No. | Analysis | Reason |
|--|-------|-----------|-------|----------------|----------|--------|
| No deviating sample report results for job 16/8520 | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

Please note that only samples that are deviating are mentioned in this report. If no samples are listed it is because none were deviating. Only analyses which are accredited are recorded as deviating if set criteria are not met.

NOTES TO ACCOMPANY ALL SCHEDULES AND REPORTS

JE Job No.: 16/8520

SOILS

Please note we are only MCERTS accredited (UK soils only) for sand, loam and clay and any other matrix is outside our scope of accreditation.

Where an MCERTS report has been requested, you will be notified within 48 hours of any samples that have been identified as being outside our MCERTS scope. As validation has been performed on clay, sand and loam, only samples that are predominantly these matrices, or combinations of them will be within our MCERTS scope. If samples are not one of a combination of the above matrices they will not be marked as MCERTS accredited.

It is assumed that you have taken representative samples on site and require analysis on a representative subsample. Stones will generally be included unless we are requested to remove them.

All samples will be discarded one month after the date of reporting, unless we are instructed to the contrary.

If you have not already done so, please send us a purchase order if this is required by your company.

Where appropriate please make sure that our detection limits are suitable for your needs, if they are not, please notify us immediately.

All analysis is reported on a dry weight basis unless stated otherwise. Results are not surrogate corrected. Samples are dried at 35°C ±5°C unless otherwise stated. Moisture content for CEN Leachate tests are dried at 105°C ±5°C.

Where Mineral Oil or Fats, Oils and Grease is quoted, this refers to Total Aliphatics C10-C40.

Where a CEN 10:1 ZERO Headspace VOC test has been carried out, a 10:1 ratio of water to wet (as received) soil has been used.

% Asbestos in Asbestos Containing Materials (ACMs) is determined by reference to HSG 264 The Survey Guide - Appendix 2 : ACMs in buildings listed in order of ease of fibre release.

Negative Neutralization Potential (NP) values are obtained when the volume of NaOH (0.1N) titrated (pH 8.3) is greater than the volume of HCl (1N) to reduce the pH of the sample to 2.0 - 2.5. Any negative NP values are corrected to 0.

WATERS

Please note we are not a UK Drinking Water Inspectorate (DWI) Approved Laboratory .

ISO17025 (UKAS) accreditation applies to surface water and groundwater and one other matrix which is analysis specific, any other liquids are outside our scope of accreditation.

As surface waters require different sample preparation to groundwaters the laboratory must be informed of the water type when submitting samples.

Where Mineral Oil or Fats, Oils and Grease is quoted, this refers to Total Aliphatics C10-C40.

DEVIATING SAMPLES

Samples must be received in a condition appropriate to the requested analyses. All samples should be submitted to the laboratory in suitable containers with sufficient ice packs to sustain an appropriate temperature for the requested analysis. If this is not the case you will be informed and any test results that may be compromised highlighted on your deviating samples report.

SURROGATES

Surrogate compounds are added during the preparation process to monitor recovery of analytes. However low recovery in soils is often due to peat, clay or other organic rich matrices. For waters this can be due to oxidants, surfactants, organic rich sediments or remediation fluids. Acceptable limits for most organic methods are 70 - 130% and for VOCs are 50 - 150%. When surrogate recoveries are outside the performance criteria but the associated AQC passes this is assumed to be due to matrix effect. Results are not surrogate corrected.

DILUTIONS

A dilution suffix indicates a dilution has been performed and the reported result takes this into account. No further calculation is required.

NOTE

Data is only reported if the laboratory is confident that the data is a true reflection of the samples analysed. Data is only reported as accredited when all the requirements of our Quality System have been met. In certain circumstances where all the requirements of the Quality System have not been met, for instance if the associated AQC has failed, the reason is fully investigated and documented. The sample data is then evaluated alongside the other quality control checks performed during analysis to determine its suitability. Following this evaluation, provided the sample results have not been effected, the data is reported but accreditation is removed. It is a UKAS requirement for data not reported as accredited to be considered indicative only, but this does not mean the data is not valid.

Where possible, and if requested, samples will be re-extracted and a revised report issued with accredited results. Please do not hesitate to contact the laboratory if further details are required of the circumstances which have led to the removal of accreditation.

Please include all sections of this report if it is reproduced

ABBREVIATIONS and ACRONYMS USED

| | |
|---------|--|
| # | ISO17025 (UKAS) accredited - UK. |
| B | Indicates analyte found in associated method blank. |
| DR | Dilution required. |
| M | MCERTS accredited. |
| NA | Not applicable |
| NAD | No Asbestos Detected. |
| ND | None Detected (usually refers to VOC and/SVOC TICs). |
| NDP | No Determination Possible |
| SS | Calibrated against a single substance |
| SV | Surrogate recovery outside performance criteria. This may be due to a matrix effect. |
| W | Results expressed on as received basis. |
| + | AQC failure, accreditation has been removed from this result, if appropriate, see 'Note' on previous page. |
| ++ | Result outside calibration range, results should be considered as indicative only and are not accredited. |
| * | Analysis subcontracted to a Jones Environmental approved laboratory. |
| AD | Samples are dried at 35°C ±5°C |
| CO | Suspected carry over |
| LOD/LOR | Limit of Detection (Limit of Reporting) in line with ISO 17025 and MCERTS |
| ME | Matrix Effect |
| NFD | No Fibres Detected |
| BS | AQC Sample |
| LB | Blank Sample |
| N | Client Sample |
| TB | Trip Blank Sample |
| OC | Outside Calibration Range |

JE Job No: 16/8520

| Test Method No. | Description | Prep Method No. (if appropriate) | Description | ISO 17025 (UKAS) | MCERTS (UK soils only) | Analysis done on As Received (AR) or Dried (AD) | Reported on dry weight basis |
|-----------------|---|----------------------------------|--|------------------|------------------------|---|------------------------------|
| TM5 | Modified USEPA 8015B method for the determination of solvent Extractable Petroleum Hydrocarbons (EPH) with carbon banding within the range C8-C40 GC-FID. | PM30 | Water samples are extracted with solvent using a magnetic stirrer to create a vortex. | Yes | | | |
| TM30 | Determination of Trace Metal elements by ICP-OES (Inductively Coupled Plasma - Optical Emission Spectrometry). Modified US EPA Method 200.7 | PM14 | Analysis of waters and leachates for metals by ICP OES. Samples are filtered for dissolved metals and acidified if required. | | | | |
| TM30 | Determination of Trace Metal elements by ICP-OES (Inductively Coupled Plasma - Optical Emission Spectrometry). Modified US EPA Method 200.7 | PM14 | Analysis of waters and leachates for metals by ICP OES. Samples are filtered for dissolved metals and acidified if required. | Yes | | | |
| TM36 | Modified US EPA method 8015B. Determination of Gasoline Range Organics (GRO) in the carbon chain range of C4-12 by headspace GC-FID. | PM12 | Modified US EPA method 5021. Preparation of solid and liquid samples for GC headspace analysis. | Yes | | | |
| TM37 | Modified USEPA 160.2. Gravimetric determination of Total Suspended Solids. Sample is filtered and the resulting residue is dried and weighed. | PM0 | No preparation is required. | Yes | | | |
| TM38 | Soluble Ion analysis using the Thermo Aquakem Photometric Automatic Analyser. Modified US EPA methods 325.2, 375.4, 365.2, 353.1, 354.1 | PM0 | No preparation is required. | | | | |
| TM58 | Modified USEPA methods 405.1 and BS 5667-3. Measurement of Biochemical Oxygen Demand. When cBOD (Carbonaceous BOD) is requested a nitrification inhibitor is added which prevents the oxidation of reduced forms of nitrogen, such as ammonia, nitrite and organic nitrogen which exert a nitrogenous demand. | PM0 | No preparation is required. | Yes | | | |
| TM73 | Modified US EPA methods 150.1 and 9045D. Determination of pH by Metrohm automated probe analyser. | PM0 | No preparation is required. | Yes | | | |
| NONE | No Method Code | NONE | No Method Code | | | | |
| | | | | | | | |